

SDMX STANDARDS: SECTION 7

GUIDELINES FOR THE USE OF WEB SERVICES

VERSION 2.1

(UPDATE APRIL 2013)

Contents

1. Introduction	6
2. Web Services and SDMX-ML	6
3. SOAP-Based SDMX Web Services: WSDL Operations and Behaviours	8
Introduction	8
The SDMX Web-Services Namespace	8
Support for WSDL Operations	8
List of WSDL Operations.....	8
3.1.1 Data	<u>98</u>
3.1.2 Metadata.....	9
3.1.3 Structure usage	9
3.1.4 Structure	<u>109</u>
3.1.5 Item scheme	10
3.1.6 Other maintainable artefacts.....	10
3.1.7 XML Schemas (XSD).....	11
3.1.8 Generic query for structural metadata	11
Other Behaviours	11
3.1.9 Versioning Defaults.....	11
3.1.10 Resolving References and Specifying Returned Objects	11
3.1.11 Enabling compression	12
3.1.12 Implementation of the SOAP based SDMX Web Services	12
3.1.13 Compliance with WS-I	12
4. SDMX RESTful API	12
A Brief Introduction to REST	12
Scope of the API	13
Structural Metadata Queries	13
4.1.1 Resources.....	13

4.1.2	Parameters	14
4.1.3	Examples	18
	Data and Metadata Queries	20
4.1.4	Resources.....	20
4.1.5	Parameters	20
4.1.6	Examples	25 24
	Schema queries	25
4.1.7	Resources.....	25
4.1.8	Parameters	26 25
4.1.9	Examples	27 26
	Selection of the Appropriate Representation	27
	Enabling data compression.....	28
5.	Standard Errors for SDMX Web Services	28
	Introduction	28
	Error handling in REST Web Service.....	29 28
	SOAP Web Service.....	29 28
	Error categories.....	29
	Client-Caused Errors.....	29
5.1.1	No results found – 100.....	29
5.1.2	Unauthorized – 110	29
5.1.3	Response Too Large Due to Client Request 130	30 29
5.1.4	Syntax error – 140	30 29
5.1.5	Semantic error – 150	30 29
	Server-Caused Errors	30
5.1.6	Internal Server Error – 500	30
5.1.7	Not implemented – 501.....	30
5.1.8	Service unavailable – 503.....	30

5.1.9	Response size exceeds service limit - 510	30
	Custom Errors – 1000+	<u>3130</u>
	SDMX to HTTP Error Mapping.....	<u>3130</u>
6.	Annex: Examples	<u>3234</u>
	Sample Queries for a Web Services Client.....	<u>3234</u>
6.1.1	Step 1: Browsing an SDMX data source, using a list of subject-matter domains <u>3234</u>	
6.1.1.3	Request using the SOAP API	32
6.1.2	STEP 2: Selecting a dataflow	33
6.1.2.3	Request using the SOAP API	34
6.1.3	STEP 3: Data selection.....	36
6.1.3.3	Request using the SOAP API	36
	Sample Error Element in an SDMX message	38
	Soap Fault example	39
7.	Annex: Security guidelines	40
7.1	Measures.....	Error! Bookmark not defined.40
7.1.1	Authentication	40
7.1.1.1	Server authentication	40
7.1.1.2	Client authentication.....	40
	Confidentiality.....	40
	Integrity	<u>4044</u>

1. Introduction

Web services represent the current generation of Internet technologies. They allow computer applications to exchange data directly over the Internet, essentially allowing modular or distributed computing in a more flexible fashion than ever before. In order to allow web services to function, however, many standards are required: for requesting and supplying data; for expressing the enveloping data which is used to package exchanged data; for describing web services to one another, to allow for easy integration into applications that use other web services as data resources.

SDMX, with its focus on the exchange of data using Internet technologies provides some of these standards relating to statistical data and metadata. Many web-services standards already exist, however, and there is no need to re-invent them for use specifically within the statistical community. Specifically, SOAP (which originally stood for the “Simple Object Access Protocol”) and the Web Services Description Language (WSDL) can be used by SDMX to complement the data and metadata exchange formats they are standardizing. In the web services world, the REST (“Representational State Transfer”) protocol is also often used, relying on a URL-based syntax to invoke web services. Such REST-based services can be described in a standard fashion using WADL (“Web Application Description Language”), in the same way that XML-invoked web services based on SOAP can be described using WSDL.

Despite the promise of SOAP and WSDL, it became evident from early implementations by vendors that these were not, in fact, interoperable. It was for this reason that the Web Services - Interoperability (WS-I) initiative was started. This consists of a group of vendors who have all implemented the same web-services standards the same way, and have verified this fact by doing interoperability tests. They publish profiles describing how to use web services standards interoperably. SDMX uses the work of WS-I as appropriate to meet the needs of the statistical community.

This document provides several SDMX-specific guidelines for using the existing standards in a fashion which will promote interoperability among SDMX web services, and allow for the creation of generic client applications which will be able to communicate meaningfully with any SDMX web service which implements these guidelines.

Much of the content of this document is not normative – instead the intention is to suggest a best practice in using SDMX-ML documents and web services standards for the exchange of statistical data and metadata. However, the SDMX WSDL and WADL files that formalise, in XML, the APIs described in this document are normative.

2. Web Services and SDMX-ML

Conventional applications and services traditionally expose their functionality through application programming interfaces (APIs). Web services are no different – they provide a public version of the function calls which can be accessed over the web using web-services protocols (SOAP or REST). In order to make a set of web services interoperate, it is necessary to have a standard abstraction, or model, on which these public functions are based. SDMX benefits from having a common information model, and it is a natural extension to use the SDMX Information Model as the basis for standard web-services function calls.

Web services exchange data in an XML format: this is how the data passed between web services is formatted. SDMX-ML, as a standard XML for exchanging data and structural metadata within the statistical realm, provides a useful XML format for the public serialization of web-services data. While there are some techniques for simple web-services data

exchanges – remote procedure calls (RPCs) – which are often used, the use of a set of XML exchanges based on a common information model is seen as a better approach for achieving interoperability.

There are several different document types available within SDMX-ML, and all are potentially important to the creators and users of SDMX web services.

1. **The "Structure" Message:** This message describes the concepts, data and metadata structure definitions, and code lists which define the structure of statistical data and reference metadata. Every SDMX-compliant data set or metadata set must have a data or metadata structure definition described for it. This XML description must be available from an SDMX web service when it is asked for.
2. **The "Generic" Data Message:** This is the "generic" way of marking up an SDMX data set. This schema describes a non-data-structure-definition-specific format for exchanging SDMX data, and it is a requirement that every SDMX data web service makes its data available in at least this form. It is expected that, in many instances, other data-structure-definition-specific XML forms for expressing data will also be supported in parallel services.
3. **The "Structure Specific" Data Message:** This is a standard schema format derived from the structure description using a standardized mapping, and many standard tags. It is specific to the structure of a particular data structure definition, and so every data structure definition will have its own "structure specific" schemas. It is designed to enable the exchange of large data sets, This is a data format that a web service may wish to provide, depending on the requirements of the data they exchange.
4. **The "Query" Messages:** This is the set of messages used to invoke SOAP-based SDMX web services. These messages all conform in a consistent way to a master template, but are decomposed into specific queries to allow each service to support only those fields in the template message which are meaningful to it. These query messages are generic across all data and metadata structure definitions, making queries in terms of the values specified for the concepts of a specific structure (as specified in a structure description). It allows users to query for data, concepts, code lists, data and metadata structure definitions.
5. **The "RegistryInterfaces" Message:** All of the Registry Interfaces are sub-elements of this SDMX-ML Message type. They are more fully described in the SDMX Registry Specification.
6. **The "Generic" Metadata Message:** This is a message used to report reference metadata concepts, which is generic across all types of reference metadata structural descriptions.
7. **The "Structure Specific" Metadata Message:** This is a message used to report reference metadata concepts specific to a particular metadata structure definition.

3. SOAP-Based SDMX Web Services: WSDL Operations and Behaviours

Introduction

This section addresses the operations and behaviours specific to SOAP-based Web Services. Most important is a list of standard WSDL operations, which will form the basis of, and be accompanied by, actual standard WSDL XML instances, for use in development packages. There are also several guidelines for the implementation of web services, to support interoperability.

All SDMX SOAP web services should be described using WSDL instances. The global element for each XML data and metadata format within SDMX should be specified as the content of the replies to each exchange. The function names for each identified pattern are specified below, along with the type of SDMX-ML payload.

Because SOAP RPC is not supported, the “parameters” of each function are simply an instance of the appropriate SDMX-ML message type. As noted above, <wsdl:import> should be used to specify the schema for a multiple-message exchange. The distributed WSDL files illustrate how SOAP messages should be used.

The bindings included in the distributed WSDL files are according to SOAP 1.1.

The SDMX Web-Services Namespace

The SDMX Web Services namespace¹ contains a set of messages specific to the use of SOAP-based services. Each of the operations described will have a message to invoke the Web-Service, and a response message. In each case, these are refinements of other SDMX messages, appropriate to the operation being performed – these are described in the list of operations, below.

Additionally, there is a list of error codes to be used in the SOAP envelope (see the [standard error codes section](#)).

Support for WSDL Operations

An SDMX web service must support all of the listed operations, even if the support is minimal, and only involves the generation of an error explaining that the requested operation has not been implemented. This is necessary for the sake of interoperability.

List of WSDL Operations

For the use of SOAP and WSDL, the Web Services Interoperability specification version 1.1 should be followed.

¹ i.e., the declared namespace of the SDMX WSDL definition.

121 **Data**

122 **3.1.1.1 GetStructureSpecificData**

123 This operation is invoked using a GetStructureSpecificDataRequest message, and receives a
124 GetStructureSpecificDataResponse as a reply.

125 **3.1.1.2 GetGenericData**

126 This operation is invoked using a GetGenericDataRequest message, and receives a
127 GetGenericDataResponse as a reply.

128 **3.1.1.3 GetStructureSpecificTimeSeriesData**

129 This operation is invoked using a GetStructureSpecificTimeSeriesDataRequest message, and
130 receives a GetStructureSpecificTimeSeriesDataResponse as a reply.

131 **3.1.1.4 GetGenericTimeSeriesData**

132 This operation is invoked using a GetGenericTimeSeriesDataRequest message, and receives
133 a GetGenericTimeSeriesDataResponse as a reply.

134 **Metadata**

135 **3.1.1.5 GetGenericMetadata**

136 This operation is invoked using a GetGenericMetadataRequest message, and receives a
137 GetGenericMetadataResponse as a reply.

138 **3.1.1.6 GetStructureSpecificMetadata**

139 This operation is invoked using a GetStructureSpecificRequest message, and receives a
140 GetStructureSpecificResponse as a reply.

141 **Structure usage**

142 **3.1.1.7 GetDataflow**

143 This operation is invoked using a GetDataflowRequest message, and receives a
144 GetDataflowResponse as a reply.

145 **3.1.1.8 GetMetadataflow**

146 This operation is invoked using a GetMetadataflowRequest message, and receives a
147 GetMetadataflowResponse as a reply.

148 **Structure**

149 **3.1.1.9 GetDataStructure**

150 This operation is invoked using a GetDataStructureRequest message, and receives a
151 GetDataStructureResponse as a reply.

152 **3.1.1.10 GetMetadataStructure**

153 This operation is invoked using a GetMetadataStructureRequest message, and receives a
154 GetMetadataStructureResponse as a reply.

155 **Item scheme**

156 **3.1.1.11 GetCategoryScheme**

157 This operation is invoked using a GetCategorySchemeRequest message, and receives a
158 GetCategorySchemeResponse as a reply.

159 **3.1.1.12 GetConceptScheme**

160 This operation is invoked using a GetConceptSchemeRequest message, and receives a
161 GetConceptSchemeResponse as a reply.

162 **3.1.1.13 GetCodelist**

163 This operation is invoked using a GetCodelistRequest message, and receives a
164 GetCodelistResponse as a reply.

165 **3.1.1.14 GetHierarchicalCodelist**

166 This operation is invoked using a GetHierarchicalCodelistRequest message, and receives a
167 GetHierarchicalCodelistResponse as a reply.

168 **3.1.1.15 GetOrganisationScheme**

169 This operation is invoked using a GetOrganisationsSchemeRequest message, and receives a
170 GetOrganisationSchemeResponse as a reply.

171 **3.1.1.16 GetReportingTaxonomy**

172 This operation is invoked using a GetReportingTaxonomyRequest message, and receives a
173 GetReportingTaxonomyResponse as a reply.

174 **Other maintainable artefacts**

175 **3.1.1.17 GetStructureSet**

176 This operation is invoked using a GetStructureSetRequest message, and receives a
177 GetStructureSetResponse as a reply.

3.1.1.18 GetProcess

This operation is invoked using a GetProcessRequest message, and receives a GetProcessResponse as a reply.

3.1.1.19 GetCategorisation

This operation is invoked using a GetCategorisationRequest message, and receives a GetCategorisationResponse as a reply.

3.1.1.20 GetProvisionAgreement

This operation is invoked using a GetProvisionAgreementRequest message, and receives a GetProvisionAgreementResponse as a reply.

3.1.1.21 GetConstraint

This operation is invoked using a GetConstraintRequest message, and receives a GetConstraintResponse as a reply.

XML Schemas (XSD)

3.1.1.22 GetDataSchema

This operation is invoked using a GetDataSchemaRequest message, and receives a GetDataSchemaResponse as a reply.

3.1.1.23 GetMetadataSchema

This operation is invoked using a GetMetadataSchemaRequest message, and receives a GetMetadataSchemaResponse as a reply.

Generic query for structural metadata

3.1.1.24 GetStructures

This operation is invoked using a GetStructuresRequest message, and receives a GetStructuresResponse as a reply.

Other Behaviours

Versioning Defaults

When no version is specified in the message invoking a service, the default is to return the last production version of the resource(s) requested.

Resolving References and Specifying Returned Objects

Version 2.1 of the SDMX-ML Query message offers new functionality to resolve reference and specify the type of objects to be returned. The SOAP API relies on this mechanism for

209 resolving references and specifying returned objects. See Section “[Applicability and meaning](#)
210 [of references attribute](#)”.

211 **Enabling compression**

212 Compression should be enabled using the appropriate HTTP Header field (Accept-Encoding).

213 **Implementation of the SOAP based SDMX Web Services**

214 In the SDMX Web Services, the development is Contract-First since the WSDL has been
215 specified by the standard. Furthermore it is a Web Service of already prepared XML
216 messages requests/responses, i.e. the interfaces for the application logic are the XML
217 messages. Therefore there is no need to generate stubs for serialisation and de-serialisation
218 of the SOAP payloads from/to the native language classes. The indicative way is to have full
219 control on the XML messages requests/responses. When using the automatic generation of
220 code it will include an extra element for the parameter of the operation in the SOAP request
221 according to the RPC paradigm, and to the SOAP specifications that is not desired according
222 to the standardised SDMX WSDL.

223 When using Apache Axis in Java, an interface for the service is offered by the toolkit that
224 reads/returns the XML payloads using DOM elements (`DOMElement` in Axis2). Moreover
225 when using the Java API for XML Web Services (JAX-WS), the developer can use the
226 `Provider<SOAPMessage>` interface, where he is responsible for creating the SOAP request
227 and response messages as well as specifying the standardised WSDL of the service.

228 However in the .NET environment there is no similar solution for this. The developer of the
229 service will have to use the `XmlAnyElement` parameter for the .NET web methods. This
230 specifies that the parameter of the Service method can be any XML element thus allows the
231 developer to take control of the XML payload. The details of this approach are presented in
232 the “Annex I: How to eliminate extra element in the .NET SDMX Web Service” in the section
233 06 of the SDMX documentation.

234 **Compliance with WS-I**

235 To ensure interoperability between SDMX web services, compliance with sections of the WS-I
236 Profile 1.1 is recommended for all SDMX web services. The documentation can be found at
237 <http://www.ws-i.org/Profiles/BasicProfile-1.1-2004-08-24.html>. The recommended sections
238 are those concerning the use of SOAP and WSDL. UDDI, while useful for advertising the
239 existence of SDMX web services, is not necessarily central to SDMX interoperability.

240 **4. SDMX RESTful API**

241 ***A Brief Introduction to REST***

242 This SDMX API is based on the REST principles, as described below:

- 243 • In REST, specific information is known as “**Resource**”. In SDMX, specific resources
244 would be, for example, code lists, concept schemes, data structure definitions,
245 dataflows, etc. Each resource is addressable via a **global identifier** (i.e.: a URI).
- 246 • Manipulating resources is done using **methods defined in the HTTP protocol** (e.g.:
247 GET, POST, PUT, DELETE). This API focuses on data retrieval, and, therefore, only
248 the usage of HTTP GET is covered in this document.

- 249 • A resource can be represented in various formats (such as the different flavours and
250 versions of the SDMX-ML standard). Selection of the appropriate **representation** is
251 done using HTTP Content Negotiation and the HTTP Accept request header.

252 *Scope of the API*

253 The RESTful API focuses on simplicity. The aim is not to replicate the full semantic richness
254 of the SDMX-ML Query message but to make it simple to perform a limited set of standard
255 queries. Also, in contrast to other parts of the SDMX specification, the RESTful API focuses
256 solely on data retrieval (via HTTP GET). More specifically, the API allows:

- 257 • To retrieve structural metadata, using a combination of id, agencyID and version
258 number.
- 259 • To retrieve statistical data or reference metadata using keys (with options for
260 wildcarding and support for the OR operator), data or metadata flows and data or
261 metadata providers.
- 262 • To further refine queries for statistical data or reference metadata using time
263 information (start period and end period).
- 264 • To retrieve updates and revisions only.
- 265 • To return the results of a query in various formats. The desired format and version of
266 the returned message will be specified using HTTP Content Negotiation (and the
267 HTTP Accept request header).
- 268 • For structural metadata, it is possible to instruct the web service to resolve references
269 (for instance, when querying for data structure definitions, it is possible to also
270 retrieve the concepts and code lists used in the returned data structure definitions),
271 as well as artefacts that use the matching artefact (for example, to retrieve the
272 dataflows that use a matching data structure definition).
- 273 • For structural metadata, it is possible to retrieve a minimal version of the artefact, for
274 the sake of efficiency (for example, to retrieve all code lists – names, ids, etc –
275 without the codes).
- 276 • A distinction should be established between the elements that allow identifying the
277 resource to be retrieved and the elements that give additional information about, or
278 allow to further filter, the desired results. Elements belonging to the 1st category are
279 specified in the path part of the URL while elements belonging to the 2nd category are
280 specified in the query string part of the URL.

281 *Structural Metadata Queries*

282 **Resources**

283 The following resources are defined:

- 284 • `datastructure`²
- 285 • `metadatastructure`³
- 286 • `categoryscheme`
- 287 • `conceptscheme`
- 288 • `codelist`
- 289 • `hierarchicalcodelist`
- 290 • `organisationscheme`⁴
- 291 • `agencyscheme`⁵

² This has been shortened from `DataStructureDefinition` to allow for shorter URLs.

³ This has been shortened from `MetadataStructureDefinition` to allow for shorter URLs.

⁴ The `organisationscheme` resource can be used whenever the role played by the organisation schemes (e.g. maintenance agencies) is not known/relevant.

- 292 • dataproviderscheme
- 293 • dataconsumerscheme
- 294 • organisationunitscheme
- 295 • dataflow
- 296 • metadataflow
- 297 • reportingtaxonomy
- 298 • provisionagreement
- 299 • structureset
- 300 • process
- 301 • categorisation
- 302 • contentconstraint
- 303 • attachmentconstraint
- 304 • structure⁶

305 Parameters

306 4.1.1.1 Parameters used for identifying a resource

307 The following parameters are used for identifying resources:

Parameter	Type	Description
agencyID	A string compliant with the SDMX common:NCNameIDType	The agency maintaining the artefact to be returned
resourceID	A string compliant with the SDMX common: IDType	The id of the artefact to be returned
version	A string compliant with the SDMX common:VersionType	The version of the artefact to be returned

308 The parameters mentioned above are specified using the following syntax:

309 protocol://ws-entry-point/resource/agencyID/resourceID/version

310 Furthermore, some keywords may be used:

Keyword	Scope	Description
all ⁷	agencyID	Returns artefacts maintained by any maintenance agency ⁸
all	resourceID	Returns all resources of the type defined by the resource parameter ⁸

⁵ For 3 of the subtypes of OrganisationScheme (AgencyScheme, DataProviderScheme and DataConsumerScheme), the id and version parameters have fixed values. See Section 03 of the SDMX information model document for additional information.

⁶ This type can be used to retrieve any type of structural metadata matching the supplied parameters.

⁷ As “all” is a reserved keyword in the SDMX RESTful API, it is recommended not to use it as an identifier for agencies, resources or a specific version.

⁸ Default, if parameter not specified

all	version	Returns all versions of the resource
latest	version	Returns the latest version in production of the resource ⁸

311

312 The following rules apply:

- 313
- If no version is specified, the version currently used in production should be returned. It is therefore equivalent to using the keyword “latest”.
- 314
- If no agencyID is specified, the matching artefacts maintained by any maintenance agency should be returned. It is therefore equivalent to using the keyword “all”⁹.
- 315
- If no resourceID is specified, all matching artefacts (according to the other criteria used) should be returned. It's is therefore equivalent to using the keyword “all”.
- 316
- If no parameters are specified, the “latest” version of “all” resources of the type identified by the resource parameter, maintained by any maintenance agency should be returned.
- 317
- 318
- 319
- 320
- 321

322 4.1.1.2 Parameters used to further describe the desired results

323 The following parameters are used to further describe the desired results, once the resource
 324 has been identified. As mentioned in 3.2, these parameters appear in the query string part of
 325 the URL.

Parameter	Type	Description	Default
detail	String	This attribute specifies the desired amount of information to be returned. For example, it is possible to instruct the web service to return only basic information about the maintainable artefact (i.e.: id, agency id, version and name). Most notably, items of item schemes will not be returned (for example, it will not return the codes in a code list query). Possible values are: “allstubs” (all artefacts should be returned as stubs ¹⁰), “referencestubs” (referenced artefacts should be returned as stubs ¹¹) and full (all available information for all artefacts should be returned ¹²) ¹³ .	full
references	String	This attribute instructs the web service to return (or not) the artefacts referenced by the artefact to be returned (for example, the code lists and concepts used by the data structure definition matching the query), as	none

⁹ This would potentially return more than one artefact, if different agencies give the same identifier to a resource (for example, http://ws-entry-point/codelist/all/CL_FREQ, could return more than one codelist if more than one agency is maintaining a codelist with id “CL_FREQ”).

¹⁰ The equivalent in SDMX-ML query is: Stub at the query level and Stub at the reference level.

¹¹ The equivalent in SDMX-ML query is: Full at the query level and Stub at the reference level.

¹² The equivalent in SDMX-ML query is: Full at the query level and Full at the reference level.

¹³ In case a stub is returned, the isExternalReference attribute of the returned artefact(s) should be set to “true” and the location where the full version of the artefact(s) can be downloaded should be specified in the structureURL attribute.

		well as the artefacts that use the matching artefact (for example, the dataflows that use the data structure definition matching the query). Possible values are: "none" (no references will be returned), "parents" (the artefacts that use the artefact matching the query), "parentsandsiblings" (the artefacts that use the artefact matching the query, as well as the artefacts referenced by these artefacts), "children" (artefacts referenced by the artefact to be returned), "descendants" (references of references, up to any level, will also be returned), "all" (the combination of parentsandsiblings and descendants). In addition, a concrete type of resource, as defined in 3.3.1 , may also be used (for example, references=codelist).	
--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--

4.1.1.3 Applicability and meaning of references attribute

The table below lists the 1st level artefacts (one level up, one level down) that will be returned if the references parameter is set to "all". Artefacts referenced by the matching artefact are displayed in regular style, while the artefacts that reference the matching artefact are displayed in *Italic*.

Maintainable artefact	Artefacts returned
AgencyScheme	<i>Categorisation</i> <i>Process</i> <i>MetadataStructureDefinition</i> <i>StructureSet</i>
Categorisation	All
CategoryScheme	<i>Categorisation</i> <i>Process</i> <i>StructureSet</i>
Codelist	<i>Categorisation</i> <i>Process</i> <i>HierarchicalCodelist</i> <i>ConceptScheme</i> <i>DataStructureDefinition</i> <i>MetadataStructureDefinition</i> <i>StructureSet</i>
ConceptScheme	<i>Categorisation</i> <i>Process</i> <i>Codelist</i> <i>DataStructureDefinition</i> <i>MetadataStructureDefinition</i> <i>StructureSet</i>
Constraint	<i>Categorisation</i> <i>Process</i> <i>DataProviderScheme</i> <i>DataStructureDefinition</i> <i>Dataflow</i>

	MetadataStructureDefinition Metadataflow ProvisionAgreement
DataConsumerScheme	<i>Categorisation</i> <i>Process</i> <i>MetadataStructureDefinition</i> <i>StructureSet</i>
Dataflow	<i>Categorisation</i> <i>Process</i> <i>Constraint</i> DataStructureDefinition ProvisionAgreement ReportingTaxonomy StructureSet
DataProviderScheme	<i>Categorisation</i> <i>Process</i> <i>Constraint</i> ProvisionAgreement <i>MetadataStructureDefinition</i> <i>StructureSet</i>
DataStructureDefinition	<i>Categorisation</i> <i>Process</i> Codelist ConceptScheme <i>Constraint</i> Dataflow StructureSet
HierarchicalCodelist	<i>Categorisation</i> <i>Process</i> Codelist StructureSet
Metadataflow	<i>Categorisation</i> <i>Process</i> <i>Constraint</i> MetadataStructureDefinition ProvisionAgreement ReportingTaxonomy StructureSet
MetadataStructureDefinition	<i>Categorisation</i> <i>Process</i> ConceptScheme Codelist DataProviderScheme DataConsumerScheme AgencyScheme OrganisationUnitScheme <i>Constraint</i> Metadataflow StructureSet

OrganisationUnitScheme	<i>Categorisation</i> <i>Process</i> <i>Constraint</i> <i>MetadataStructureDefinition</i> <i>StructureSet</i>
Process	All
ProvisionAgreement	<i>Categorisation</i> <i>Process</i> DataProviderScheme Dataflow Metadataflow <i>Constraint</i>
ReportingTaxonomy	<i>Categorisation</i> <i>Process</i> Dataflow Metadataflow <i>StructureSet</i>
StructureSet	<i>Categorisation</i> <i>Process</i> DataStructureDefinition MetadataStructureDefinition CategoryScheme DataProviderScheme DataConsumerScheme AgencyScheme OrganisationUnitScheme ConceptScheme Codelist ReportingTaxonomy HierarchicalCodelist Dataflow Metadataflow

Examples

- To retrieve version 1.0 of the DSD with id ECB_EXR1 maintained by the ECB, as well as the code lists and the concepts used in the DSD:

http://ws-entry-point/datastructure/ECB/ECB_EXR1/1.0?references=children

- To retrieve the latest version in production of the DSD with id ECB_EXR1 maintained by the ECB, without the code lists and concepts of the DSD:

http://ws-entry-point/datastructure/ECB/ECB_EXR1

- To retrieve all DSDs maintained by the ECB, as well as the dataflows using these DSDs:

<http://ws-entry-point/datastructure/ECB?references=dataflow>

342 - To retrieve the latest version in production of all code lists maintained by all maintenance
343 agencies, but without the codes:

344 <http://ws-entry-point/codelist?detail=allstubs>

345 - To retrieve, as stubs, the latest version in production of all maintainable artefacts maintained
346 by the ECB:

347 <http://ws-entry-point/structure/ECB?detail=allstubs>

348

349 **Data and Metadata Queries**

350 **Resources**

351 The following resources should be supported:

- 352 • data
- 353 • metadata

354 **Parameters**

355 **4.1.1.4 Parameters used for identifying a resource**

356 The following parameters are used for identifying resources in data queries:

Parameter	Type	Description
flowRef ¹⁴	<p>A string identifying the dataflow. The syntax is agency id, artefact id, version, separated by a “,”. For example: AGENCY_ID,FLOW_ID,VERSION</p> <p>In case the string only contains one out of these 3 elements, it is considered to be the flow id, i.e. all,FLOW_ID,latest</p> <p>In case the string only contains two out of these 3 elements, they are considered to be the agency id and the flow id, i.e. AGENCY_ID,FLOW_ID,latest</p>	The data (or metadata) flow of the data (or metadata) to be returned
key	A string compliant with the KeyType defined in the SDMX WADL.	<p>The key of the artefact to be returned. Wildcarding is supported by omitting the dimension code for the dimension to be wildcarded. For example, if the following series key identifies the bilateral exchange rates for the daily US dollar exchange rate against the euro, D.USD.EUR.SP00.A, then the following series key can be used to retrieve the data for all currencies against the euro: D..EUR.SP00.A. The OR operator is supported using the + character. For example, the following series key can be used to retrieve the exchange rates against the euro for both the US dollar and the Japanese Yen:</p>

¹⁴ It's a common use case in SDMX-based web services that the flow id is sufficient to uniquely identify a dataflow. Should this not be the case, the agency id and the dataflow version, can be used, in conjunction with the flow id, in order to uniquely identify a dataflow.

		D.USD+JPY.EUR.SP00.A.
providerRef ¹⁵	<p>A string identifying the provider. The syntax is agency id, provider id, separated by a “,”. For example: AGENCY_ID,PROVIDER_ID.</p> <p>In case the string only contains one out of these 2 elements, it is considered to be the provider id, i.e. all,PROVIDER_ID.</p>	The provider of the data (or metadata) to be retrieved. If not supplied, the returned message will contain data (or metadata) provided by any provider.

357

358 The parameters mentioned above are specified using the following syntax:

359 protocol://ws-entry-point/resource/flowRef/key/providerRef

360 Furthermore, some keywords may be used:

Keyword	Scope	Description
all	key	Returns all data belonging to the specified dataflow and provided by the specified provider.
all ¹⁶	providerRef	Returns all data matching the supplied key and belonging to the specified dataflow that has been provided by any data provider.

361

362 The following rules apply:

- 363 • If no key is specified, all data (or metadata) belonging to the dataflow (or
364 metadataflow) identified by the flowRef should be supplied. It is therefore equivalent
365 to using the keyword “all”.
- 366 • If no providerRef is specified, the matching data (or metadata) provided by any data
367 provider should be returned. It is therefore equivalent to using the keyword “all”.

368 4.1.1.5 Parameters used to further filter the desired results

369 The following parameters are used to further describe (or filter) the desired results, once the
370 resource has been identified. As mentioned in [3.2](#), these parameters go in the query string
371 part of the URL.

Parameter	Type	Description
startPeriod	common:StandardTimePeriodType, as defined in the	The start period for which results should be supplied

¹⁵ It's a common use case in SDMX-based web services that the provider id is sufficient to uniquely identify a data provider. Should this not be the case, the agency can be used, in conjunction with the provider id, in order to uniquely identify a data provider.

¹⁶ As “all” is a reserved keyword in the SDMX RESTful API, it is recommended not to use it as an identifier for providers.

	<p>SDMXCommon.xsd schema.</p> <p>Can be expressed using¹⁷:</p> <ul style="list-style-type: none"> • dateTime: all data that falls between the calendar dates will be matched • Gregorian Period: all data that falls between the calendar dates will be matched • Reporting Period: all data reported as periods that fall between the specified periods will be returned. When comparing reporting weeks and days to higher order periods (e.g. quarters) one must account for the actual time frames covered by the periods to determine whether the data should be included. Data reported as Gregorian periods or distinct ranges will be returned if it falls between the specified reporting periods, based on a reporting year start day of January 1. <p>In case the : or + characters are used, the parameter must be percent-encoded by the client¹⁸.</p> <p>Note that this value is assumed to be inclusive to the range of data being sought.</p>	(inclusive).
endPeriod	Same as above	The end period for which results should be supplied (inclusive).
updatedAfter	xs:dateTime	The last time the query was performed by the client in the database. If this attribute is used, the returned message should only include the latest

¹⁷ For additional information, see section 4.2.14 of Section 06 (SDMX Technical Notes).

¹⁸ See http://en.wikipedia.org/wiki/URL_encoding#Percent-encoding_reserved_characters for additional information.

		<p>version of what has changed in the database since that point in time (updates and revisions). This should include:</p> <ul style="list-style-type: none"> - Observations¹⁹ that have been added since the last time the query was performed (INSERT). - Observations that have been revised since the last time the query was performed (UPDATE). - Observations that have been deleted since the last time the query was performed (DELETE). <p>If no offset is specified, default to local time of the web service.</p>
firstNObservations	Positive integer	Integer specifying the maximum number of observations to be returned for each of the matching series, starting from the first observation
lastNObservations	Positive integer	Integer specifying the maximum number of observations to be returned for each of the matching series, counting back from the most recent observation
dimensionAtObservation	A string compliant with the SDMX common:NCNameIDType	The ID of the dimension to be attached at the observation level. This parameter allows the client to indicate how the data should be packaged by the service. The options are "TIME_PERIOD" (a timeseries view of the data), the ID of any other dimension used in that dataflow (a cross-sectional

¹⁹ If the information about when the data has been updated is not available at the observation level, the web service should return either the series that have changed (if the information is attached at the series level) or the dataflows that have changed (if the information is attached at the dataflow level).

		<p>view of the data) or the keyword "AllDimensions" (a "flat" view of the data where the observations are grouped neither by time nor by a non-time cross section). In case this parameter is not set, the service is expected to:</p> <ul style="list-style-type: none"> - Default to TimeDimension, if the data structure definition has one; - If not, default to MeasureDimension, if the data structure definition has one; - If none of the above is true, default to AllDimensions.
detail	String	<p>This attribute specifies the desired amount of information to be returned. For example, it is possible to instruct the web service to return data only (i.e. no attributes). Possible options are: "full" (all data and documentation, including annotations - This is the default), "dataonly" (attributes – and therefore groups – will be excluded from the returned message), "serieskeyonly" (returns only the series elements and the dimensions that make up the series keys. This is useful for performance reasons, to return the series that match a certain query, without returning the actual data), "nodata" (returns the groups and series, including attributes and annotations, without observations).</p>

372

373 The table below defines the meaning of parameters combinations:

startPeriod with no endPeriod	Until the most recent
endPeriod and no startPeriod	From the beginning
startPeriod and endPeriod	Within the supplied time range
lastNObservations + startPeriod/endPeriod	The specified number of observations, starting from the end, within the supplied time range
firstNObservations + startPeriod/endPeriod + updatedAfterDate	The specified number of observations, starting from the beginning, that have changed since the supplied timestamp, within the supplied time range
updatedAfterDate + startPeriod/endPeriod	The observations, within the supplied time range, that have changed since the supplied timestamp.

Examples

- To retrieve the data for the series M.USD.EUR.SP00.A supplied by the ECB for the ECB_EXR1_WEB dataflow:

http://ws-entry-point/data/ECB_EXR1_WEB/M.USD.EUR.SP00.A/ECB

In this example, the assumption is made that the dataflow id (ECB_EXR1_WEB) is sufficient to uniquely identify the dataflow, and the data provider id (ECB) is sufficient to uniquely identify the data provider.

- To retrieve the data, provided by the ECB for the ECB_EXR1_WEB dataflow, for the supplied series keys, using wildcarding for the second dimension:

http://ws-entry-point/data/ECB,ECB_EXR1_WEB/latest/M..EUR.SP00.A/ECB

In this example, the full reference to the dataflow is supplied (ECB as maintenance agency, ECB_EXR1_WEB as dataflow id and latest for the version).

- To retrieve the updates and revisions for the data matching the supplied series keys, using the OR operator for the second dimension, and using percent encoding for the updatedAfterDate:

[http://ws-entry-point/Data/ECB_EXR1_WEB/M.USD+GBP+JPY.EUR.SP00.A?updatedAfter=2009-05-15T14 %3A 15 %3A 00%2B01%3A00](http://ws-entry-point/Data/ECB_EXR1_WEB/M.USD+GBP+JPY.EUR.SP00.A?updatedAfter=2009-05-15T14%3A15%3A00%2B01%3A00)

- To retrieve the data matching the supplied series key and restricting the start and end dates:

http://ws-entry-point/data/ECB_EXR1_WEB/D.USD.EUR.SP00.A?startPeriod=2009-05-01&endPeriod=2009-05-31

Schema queries

Resources

The following resource is defined:

- schema

This resource allows a client to ask a service to return an XML schema, which defines data (or reference metadata) validity within a certain context. The service must take into account the constraints that apply within that context (DSD or MSD, dataflow or metadataflow, or provision agreement).

Parameters

4.1.1.6 Parameters used for identifying a resource

The following parameters are used for identifying resources:

Parameter	Type	Description
context	One of the following: datastructure, metadatastructure, dataflow, metadataflow or provisionagreement.	The value of this parameter determines the constraints that need to be taken into account, when generating the schema. If datastructure or metadatastructure is used, constraints attached to the DSD or MSD must be applied when generating the schema. If dataflow or metadataflow is used, constraints attached to the dataflow or metadataflow and to the DSD or MSD used in the dataflow or metadataflow must be applied when generating the schema. If provisionagreement is used, constraints attached to the provision agreement, as well as to the dataflow or metadataflow used in the agreement and the DSD or MSD used in the dataflow or metadataflow must be applied when generating the schema.
agencyID	A string compliant with the SDMX common:NCNameIDType	The agency maintaining the artefact used to generate the schema to be returned.
resourceID	A string compliant with the SDMX common: IDType	The id of the artefact used to generate the schema to be returned.
version	A string compliant with the SDMX common:VersionType	The version of the artefact used to generate the schema to be returned.

The parameters mentioned above are specified using the following syntax:

protocol://ws-entry-point/schema/context/agencyID/resourceID/version

Furthermore, a keyword may be used²⁰:

Keyword	Scope	Description
latest	version	Returns the latest version in production of the resource ⁸

²⁰ As the query for schema must match one artefact only, the keyword “all” is not supported for agencyId and resourceId.

412

413 The following rules apply:

- 414 • If no version attribute is specified, the version currently used in production should be
- 415 returned. It is therefore equivalent to using the keyword "latest".

416 **4.1.1.7 Parameters used to further describe the desired results**

417 The following parameters are used to further describe the desired results, once the resource
418 has been identified:

Parameter	Type	Description
dimensionAtObservation	A string compliant with the SDMX common: NCNameIDType	The ID of the dimension to be attached at the observation level.
explicitMeasure	Boolean	For cross-sectional data validation, indicates whether observations are strongly typed (defaults to false).

419 **Examples**

420

421 - To retrieve the schema for data supplied within the context of version 1.0 of the provision
422 agreement EXR_WEB maintained by the ECB:

423 [http://ws-entry-point/schema/provisionagreement/ECB/ EXR_WEB/1.0/](http://ws-entry-point/schema/provisionagreement/ECB/EXR_WEB/1.0/)

424 In this case, the schema returned by the service must take into account the
425 constraints attached to the provision agreement, the dataflow used in the provision
426 agreement and the data structure definition used in the dataflow.

427 ***Selection of the Appropriate Representation***

428 Selection of the appropriate formats for the response message is made using the
429 mechanisms defined for HTTP Content Negotiation²¹. Using the HTTP Content Negotiation
430 mechanism, the client specifies the desired format and version of the resource using the
431 Accept HTTP header²².

432 Along with official mime types (e.g.: text/html, application/xml, etc), the standard also defines
433 a syntax allowing a service to define its own types. The SDMX Restful API makes use of this
434 functionality and the syntax is as follows:

435 application/vnd.sdmx.[format]+xml;version=[version]²³, where [format] should be replaced with
436 the desired format (i.e. : genericdata, structurespecificdata, structure, etc) and [version]
437 should be replaced with one of the versions of the SDMX standard, starting with SDMX 2.1
438 (e.g.: 2.1, future SDMX versions, etc).

²¹ For additional information, please refer to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec12.html>

²² For additional information, please refer to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html>

²³ For the time being, only version 2.1 is supported as version number.

439 A few examples are listed below

- 440 • SDMX-ML Generic Data Format, version 2.1:
441 application/vnd.sdmx.genericdata+xml;version=2.1
- 442 • SDMX-ML Structure Specific Data Format, version 2.1:
443 application/vnd.sdmx.structurespecificdata+xml;version=2.1
- 444 • SDMX-ML Structure Format, version 2.1:
445 application/vnd.sdmx.structure+xml;version=2.1
446

447 In case the client does not specify the desired format and version of the response message,
448 or only specifies the generic application/xml format, the SDMX RESTful web service should
449 return:

- 450 • The most recent version, that the service supports, of the SDMX-ML Structure format
451 for structural metadata queries;
- 452 • The most recent version, that the service supports, of the SDMX-ML Generic Data
453 format for data queries;
- 454 • The most recent version, that the service supports, of the SDMX-ML Generic
455 Metadata format for metadata queries.
456

457 The list below indicates the valid formats for SDMX RESTful web services, compliant with
458 version 2.1 of the SDMX standard:

- 459 • application/vnd.sdmx.genericdata+xml;version=2.1
- 460 • application/vnd.sdmx.structurespecificdata+xml;version=2.1
- 461 • application/vnd.sdmx.generictimeseriesdata+xml;version=2.1
- 462 • application/vnd.sdmx.structurespecifictimeseriesdata+xml;version=2.1
- 463 • application/vnd.sdmx.genericmetadata+xml;version=2.1
- 464 • application/vnd.sdmx.structurespecificmetadata+xml;version=2.1
- 465 • application/vnd.sdmx.structure+xml;version=2.1
- 466 • application/vnd.sdmx.schema+xml;version=2.1

467 ***Enabling data compression***

468 Compression should be enabled using the appropriate HTTP Header field (Accept-
469 Encoding).

470 **5. Standard Errors for SDMX Web Services**

471 ***Introduction***

472 In SDMX-ML version 2.1 an error element has been implemented in all messages that would
473 normally be a response to a query, that is: Structure, MetadataStructure, GenericData,
474 DSDData and Metadata. In case of an error the error element will be added to the
475 structure:Structures | generic:GenericDataSet | message:DataSet |
476 genericmetadata:MetadataSet | metadatareport:MetadataSet element in the response
477 message.

478 The element belongs to Message schemas and use the StatusTextType from the Common
479 schema file. In the end of this document is an extract from the schema files showing the error
480 element.

481 The error part of the XML message supports the 2 following use cases:

- 482 • Any error which is detected before SDMX data is streamed to the client will be
483 returned in the Error element defined in the SDMX message namespace.
484 • If the error occurs after some SDMX data has already been streamed to the client,
485 the error information will be supplied via a “footer” element in the SDMX payload.

486 ***Error handling in REST Web Service***

487 RESTful web services should indicate errors using the proper HTTP status code. In addition,
488 whenever appropriate, the error should also be returned using the error message offered
489 starting with version 2.1 of SDMX-ML.

490 ***SOAP Web Service***

491 SOAP web services should indicate errors using the standard SOAP error mechanism, using
492 the specific namespace created for this purpose. In addition, whenever appropriate²⁴, the
493 error should also be returned using the error message offered starting with version 2.1 of
494 SDMX-ML.

495 In case of error, the following elements should be set in the SOAP Envelope:

- 496 • the <faultcode> element for the error number
497 • the <faultstring> element for the description
498 • the <faultactor> element for the webservice method with the url for the webservice
499 prefixed
500 • The <detail> element is optional, and can be used by the service provider to provide
501 any additional information deemed useful

502 ***Error categories***

503 The numbering of error messages divides the three types of messages up, and provides for
504 web services to implement custom messages as well:

- 505 • 000 – 499: Client-caused "errors"
506 • 500 – 999: Server-caused "errors"
507 • 1000 and up: Custom Messages

508 ***Client-Caused Errors***

509 **No results found – 100**

510 There is no difference between SOAP and REST webservices for this message. If the result
511 from the query is empty the webservice should return this message. This is a way to inform
512 the client that the result is empty.

513 **Unauthorized – 110**

514 For use when authentication is needed but has failed or has not yet been provided.

²⁴ According to the SOAP version Framework 1.2, it is not possible to place both a <faultcode> element and return other information.

Response Too Large Due to Client Request 130

The request results in a response that is larger than the client is willing or able to process. The client has the possibility, using SDMX-ML query, to limit the size of the response returned by the server. In case the response is larger than the limit set by the client, the server should return this error code.

Syntax error – 140

This error code is used when:

- SOAP: The supplied SDMX-ML Query message is invalid (XML validation fails)

- REST: The query string doesn't comply with the SDMX RESTful interface.

Semantic error – 150

A web service should return this error when a request is syntactically correct but fails a semantic validation or violates agreed business rules.

Server-Caused Errors

Internal Server Error – 500

The webservice should return this error code when none of the other error codes better describes the reason for the failure of the service to provide a meaningful response.

Not implemented – 501

If the webservice has not yet implemented one of the methods defined in the API, then the webservice should return this error.

Note: All SDMX web services should implement all the standard interfaces, even if their only function is to return this error message. This eases interoperability between SDMX-compliant web services and it also eases the development of generic SDMX web services clients.

Service unavailable – 503

If a web service is temporarily unavailable because of maintenance or for some other similar reasons, then the webservice should return this error code.

Response size exceeds service limit - 510

The request results in a response that is larger than the server is willing or able to process.

In case the service offers the possibility to users to download the results of large queries at a later stage (for instance, using asynchronous web services), the web service may choose to indicate the (future) location of the file, as part of the error message. In SOAP, this can be done using the error element <faultstring>.

Custom Errors – 1000+

Web services can use codes 1000 and above for the transmission of service-specific error messages. However, it should be understood that different services may use the same numbers for different errors, so the documentation provided by the specific service should be consulted when implementing this class of errors.

SDMX to HTTP Error Mapping

The following table maps the SDMX error codes with the HTTP status code for RESTful web services and indicates how the errors should be returned in SOAP.

SDMX error	HTTP error usage in REST	SOAP usage
Client errors		
100 No results found	404 Not found	SOAP Fault
110 Unauthorized	401 Unauthorized	SOAP Fault
130 Response too large due to client request	413 Request entity too large	SOAP Fault
140 Syntax error	400 Bad syntax	SOAP Fault
150 Semantic error	400 Bad syntax	SOAP Fault
Server errors		
500 Internal Server error	500 Internal server error	SOAP Fault
501 Not implemented	501 Not implemented	SOAP Fault
503 Service unavailable	503 Service unavailable	SOAP Fault
510 Response size exceeds service limit	413 Request entity too large	Payload
1000+	500 Internal server error	SOAP Fault


6. Annex: Examples

Sample Queries for a Web Services Client

Step 1: Browsing an SDMX data source, using a list of subject-matter domains

6.1.1.1 Use case

The web client offers the possibility to retrieve data by browsing a list of subject matter domains. The client requests the version currently in production of the SDW_ECON category scheme, maintained by the ECB.



6.1.1.2 Request using the RESTful API

http://ws-entry-point/categoryscheme/ECB/SDW_ECON?references=categorisation

Note: Using the references attribute with a value of “categorisation”, the categorisations used by the category scheme will also be returned and these will contain references to the dataflows attached to the categories.

6.1.1.3 Request using the SOAP API

```
<query:CategorySchemeQuery referenceResolution="Shallow">
  <query:References>
    <query:Default/>
  </query:References>
  <query:CategorySchemeWhere>
    <query:ID>SDW_ECON</query:ID>
    <query:AgencyID>ECB</query:AgencyID>
  </query:CategorySchemeWhere>
</query:CategorySchemeQuery>
```



```
576         </query:CategorySchemeWhere>
577     </query:CategorySchemeQuery>
578
```

579 Note: For the sake of clarity, the SOAP envelope has been omitted.

580 **6.1.1.4 Response**


581 An SDMX-ML Structure message containing the category schemes, as well as the
 582 categorisations with references to the dataflows will be returned. The structure of the SDMX-
 583 ML Structure message will be as follow (root element, header and repeated elements omitted
 584 for the sake of clarity):

```
585 <structure:Structures>
586     <structure:CategorySchemes>
587         <structure:CategoryScheme>
588     </structure:CategoryScheme>
589 </structure:CategorySchemes>
590 <structure:Categorisations>
591     <structure>DataflowCategorisation>
592 </structure>DataflowCategorisation>
593 </structure:Categorisations>
594 </structure:Structures>
```

595 **STEP 2: Selecting a dataflow**

596 **6.1.1.5 Use case**

597 Once a subject-matter domain and a dataflow have been selected, a filter box needs to be
 598 populated, to allow users to select data. In order to only create queries for data that actually
 599 exist in the database, the dataflow constraints will also be requested.



6.1.1.6 Request using the RESTful API

In this sample query, the dataflow id is 123456, the agency id is ECB and the version is 1.2. Using the references attribute, the data structure definition and the constraints will also be returned.

`http://ws-entry-point/dataflow/ECB/123456/1.2?references=all`

6.1.1.7 Request using the SOAP API

```
<query>DataflowQuery>
  <query:References>
    <query:Default/>
  </query:References>
  <query>DataflowWhere>
    <query:ID>123456</query:ID>
    <query:Version>1.2</query:Version>
    <query:AgencyID>ECB</query:AgencyID>
  </query>DataflowWhere>
</ query>DataflowQuery>
```

6.1.1.8 Response


An SDMX-ML Structure message containing the requested dataflow, as well as the data structure definition and the dataflow constraints attached. The structure of the SDMX-ML Structure message will be as follows (root element and header omitted):

```

621 <structure:Structures>
622     <structure>Dataflows>
623         <structure>Dataflow>
624         </structure>Dataflow>
625     </structure>Dataflows>
626     <structure:Codelists>
627     </structure:Codelists>
628     <structure:Concepts>
629     </structure:Concepts>
630     <structure>DataStructures>
631     </structure>DataStructures>
632     <structure:Constraints>
633         <structure:ContentConstraint>
634         </structure:ContentConstraint>
635     </structure:Constraints>
636 </structure:Structures>
637

```

If, before selecting data, the user wants to review the data structure definition used by the dataflow, this can be done without sending an additional query, as this information has already been included in the response.




ID	Concept	Allowed values
FREQ	Frequency	Annual
REF_AREA	Reference area	International organisations
ADJUSTMENT	Adjustment indicator	Trend-cycle data, working day adjusted, not seasonally adjusted
DATA_TYPE_BOP	Data type - BoP related data	Outstanding amounts at the beginning of the period (stocks)
BOP_ITEM	Balance of Payment item	Current and capital account
CURR_BRKDOWN	Currency breakdown	Euro
COUNT_AREA	Counterpart area	International organisations
SERIES_DENOM	Series denominat/spec calcul	3 month annualised growth rate
TIME_PERIOD	Time period or range	

ID	Concept	Attachment Level	Allowed values
AGG_EQUN	Aggregation equations	Group	Up to 350
COMPILATION	Compilation	Group	Up to 1050
DECIMALS	Decimals	Group	Zero
SOURCE_AGENCY	Source agency	Group	International organisations
TITLE	Title	Group	Up to 70
TITLE_COMPL	Title complement	Group	Up to 1050
UNIT	Unit	Group	Andorran franc (1-1 peg to the French franc)
UNIT_MULT	Unit multiplier	Group	Hundredth
BOP_BASIS	BoP data collection basis	Series	Transaction (only for flows)
BREAKS	Breaks	Series	Up to 350
COLLECTION	Collection indicator	Series	Average of observations through period
PUBL_ECB	Source publication (ECB only)	Series	Up to 1050

STEP 3: Data selection

6.1.1.9 Use case

The user uses the dimension filters, to retrieve the data he is interested in.



6.1.1.10 Request using the RESTful API

<http://ws-entry-point/data/123456/M.14.N.9.339+340+341.N.A1.A/ECB?startPeriod=2009-01&endPeriod=2009-12&detail=dataonly>

Note: Apart from the dataflow id (123456), the data provider is set to ECB, and the series key uses the OR operator for the 5th dimension. Furthermore, only data for 2009 should be returned. As the purpose of the returned data is to be displayed on a graph, the detail level is set to data only. Therefore, attributes and groups will be excluded from the returned message. Regarding the references to the dataflow, the short form is used, as, for this particular web service, the dataflow id and the data provider id are sufficient to uniquely identify the dataflow and the data provider respectively. Should this not be the case, the full reference must be supplied (for example, ECB+123456+1.2 instead of 123456).

6.1.1.11 Request using the SOAP API

```
<query:Query>
  <query:DataWhere>
    <query:DataProvider>
      <common:OrganisationSchemeRef>
```

```

662         <common:AgencyID>ECB</common:AgencyID>
663         <common:ID>DataProviderScheme</common:ID>
664         </common:OrganisationSchemeRef>
665         <common:DataProviderRef>
666             <common:ID>ECB</common:ID>
667         </common:DataProviderRef>
668     </query:DataProvider>
669     <query:StructureUsage>
670         <common:DataflowReference>
671             <common:Ref>
672                 <common:AgencyID>ECB</common:AgencyID>
673                 <common:ID>123456</common:ID>
674                 <common:Version>1.2</common:Version>
675             </common:Ref>
676         </common:DataflowReference>
677     </query:StructureUsage>
678     <query:DimensionValue>
679         <query:ID>FREQ</query:ID>
680         <query:Value>M</query:Value>
681     </query:DimensionValue>
682     <query:DimensionValue>
683         <query:ID>REF_AREA</query:ID>
684         <query:Value>I4</query:Value>
685     </query:DimensionValue>
686     <query:DimensionValue>
687         <query:ID>ADJUSTMENT</query:ID>
688         <query:Value>N</query:Value>
689     </query:DimensionValue>
690     <query:DimensionValue>
691         <query:ID>DATA_TYPE_BOP</query:ID>
692         <query:Value>9</query:Value>
693     </query:DimensionValue>
694     <query:DimensionValue>
695         <query:ID>CURR_BRKDOWN</query:ID>
696         <query:Value>N</query:Value>
697     </query:DimensionValue>
698     <query:DimensionValue>
699         <query:ID>COUNT_AREA</query:ID>
700         <query:Value>A1</query:Value>
701     </query:DimensionValue>
702     <query:DimensionValue>
703         <query:ID>SERIES_DENOM</query:ID>
704         <query:Value>A</query:Value>
705     </query:DimensionValue>
706     <query:TimeDimensionValue>
707         <query:ID>TIME_PERIOD</query:ID>
708         <query:TimeValue>
709 operator="GreaterThanOrEqualTo">2009-01</query:TimeValue>
710         <query:TimeValue>
711 operator="LessThanOrEqualTo">2010-12</query:TimeValue>
712     </query:TimeDimensionValue>
713     <query:Or>

```

```

714         <query:DimensionValue>
715             <query:ID>BOP_ITEM</query:ID>
716             <query:Value>339</query:Value>
717         </query:DimensionValue>
718         <query:DimensionValue>
719             <query:ID>BOP_ITEM</query:ID>
720             <query:Value>340</query:Value>
721         </query:DimensionValue>
722         <query:DimensionValue>
723             <query:ID>BOP_ITEM</query:ID>
724             <query:Value>341</query:Value>
725         </query:DimensionValue>
726     </query:Or>
727 </query:DataWhere>
728 </query:Query>

```

6.1.1.12 Response

730 An SDMX-ML Generic data message containing the requested time series.

731 The structure of the SDMX-ML Data message will be as follows (root element and header
732 omitted):

```

733 <message:DataSet>
734     <generic:Series>
735     </generic:Series>
736 </message:DataSet>

```

Sample Error Element in an SDMX message

```

737
738 <xs:element name="Error" type="ErrorType">
739     <xs:annotation>
740         <xs:documentation>Error is used to communicate
741             that an error has occurred when responding to a
742             request in an non-registry environment. The
743             content will be a collection of error messages.
744         </xs:documentation>
745     </xs:annotation>
746 </xs:element>
747 <xs:complexType name="ErrorType">
748     <xs:annotation>
749         <xs:documentation>ErrorType describes the
750             structure of an error response.
751         </xs:documentation>
752     </xs:annotation>
753     <xs:sequence>
754         <xs:element name="ErrorMessage"
755             type="common:StatusTextType" maxOccurs="unbounded">
756             <xs:annotation>
757                 <xs:documentation>ErrorMessage
758                     contains the error message. It can
759                     occur multiple times to communicate

```

```

760         message for multiple errors, or to
761         communicate the error message in
762         parallel languages. If both messages
763         for multiple errors and parallel
764         language messages are used, then each
765         error message should be given a code
766         in order to distinguish message for
767         unique errors.
768         </xs:documentation>
769     </xs:annotation>
770 </xs:element>
771 </xs:sequence>
772 </xs:complexType>

```

773 ***Soap Fault example***

```

774 <?xml version = "1.0" encoding = "UTF-8" ?>
775 <soapenv:Envelope
776 xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
777 xmlns:xsd="http://www.w3.org/2001/XMLSchema"
778 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
779 xmlns:sdmxerror="http://www.SDMX.org/resources/SDMXML/webservice/iso/v\_2\_0\_draft/error"
780
781
782 xmlns:sdmxws="http://www.SDMX.org/resources/SDMXML/webservice/iso/v\_2\_0\_draft">
783 <soapenv:Body>
784 <soapenv:Fault>
785 <faultcode>sdmxerror:500</faultcode>
786 <faultstring>Internal server error</faultstring>
787 <faultactor>sdmxws:GetCodelist</faultactor>
788 <detail>
789 <sdmxws:composite>
790 <sdmxws:code>1028</sdmxws:code>
791 <sdmxws:titles>
792 <sdmxws:title lang="de">Could not get connection from pool</sdmxws:title>
793 <sdmxws:title lang="en">Could not get connection from pool</sdmxws:title>
794 <sdmxws:title lang="fr">Could not get connection from pool</sdmxws:title>
795 </sdmxws:titles>
796 <sdmxws:source>SdmxRegistryService error: could not get connection from
797 pool</sdmxws:source>
798 </sdmxws:composite>
799 </detail>
800 </soapenv:Fault>
801 </soapenv:Body>
802 </soapenv:Envelope>
803

```

7. Annex: Security guidelines

This annex describes useful security measures for SDMX web services²⁵.

Authentication

Authentication refers to the process of uniquely identifying an entity. In the context of a web service, service authentication and client authentication are distinct.

Server authentication

Clients of web services have a high interest in ensuring that they are connected to the service they intend to consume and not to a rogue service masquerading as a trusted entity. To support this, use SSL/TLS²⁶ and offer clients the possibility to consume the web service over HTTPS.

Client authentication

When restrictions apply to the data and metadata published, it is important for the service provider to be able to uniquely identify the client.

For RESTful web services, support this requirement by using HTTP basic authentication over SSL/TLS²⁷. If stronger authentication is required, use SSL client certificates instead.

HTTP basic authentication over SSL/TLS can also be used to support authentication in SOAP web services. In situations where this is not appropriate, use industry standard such as OASIS Web Services Security (WSS) Specification. Use and declare a standard token profile in WS-Policy assertions. Include and explicitly declare WS Security assertions and requirements the WSDL file with a standard targeted namespace and security token information.

Confidentiality

Confidentiality refers to the process of guaranteeing that resources cannot be accessed by unauthorised users.

This requirement is a key requirement for the SDMX web services when restrictions apply to the data and metadata published, as both clients and services have a high interest in ensuring their data is not illegally accessed. For these web services, use SSL/TLS²⁸ to support confidentiality during the transfer between the service and the client using.

Integrity

Integrity refers to the process of guaranteeing that resources cannot be accidentally or maliciously modified.

²⁵ This annex is not comprehensive, as security-related measures for SDMX web services will vary according to the scope of the web service and the security policies of the organisation maintaining the web service.

²⁶ This allows the client to validate that the certificate matches the domain name of the service, is issued by a trusted authority, and is not expired.

²⁷ See [RFC 2617](#) for additional information.

²⁸ SSL/TLS supports this requirement using a combination of symmetric and asymmetric encryption.

835 Support this requirement using SSL/TLS²⁹.

²⁹ SSL/TLS supports this requirement by calculating a message digest.